

# *au* BP-9000E



**24** PIN

## Business Advantage

Heavy - Duty and High speed Printing in Graphic Mode!

- High speed  
*au* BP-9000E 846cps (SSD mode, 15dpi)
- 7 resident LQ fonts
- 1+8 multipart forms capability
- 2 emulation modes : EPSON ESC/P IBM 2391
- 132Kbyte data buffer
- Interface : Centronics (IEEE 1284 NIBBLE), RS-232C  
USB (USB2.0 Full-speed), 10/100 Base-T Ethernet



## Specifications

**au**i BP-9000E

<b>Print method</b>	24-pin dot matrix impact / bi-directional (text & graphics)
<b>Print speed</b>	Super Speed Draft (15cpi) : 846cps Speed Draft (12cpi) : 676cps Draft pica (10cpi) : 564cps HQDR pica (10cpi) : 360cps NLQ pica (10cpi) : 240cps LQ pica (10cpi) : 180cps
<b>Graphic print speed</b>	10.5 ips, or 18.0 ips or 24.0 ips (180/360DPI) 15.7 ips, or 18.0 ips or 31.5 ips (120/240DPI)
<b>Line feed speed</b>	60 or 30 lines/second (6 lines/inch) selectable
<b>Line feed pitch</b>	1/360"
<b>Emulation</b>	EPSON ESC/P, IBM 2391
<b>Data buffer</b>	132 Kbytes
<b>Resident fonts</b>	Roman, Sans-serif, Courier, Prestige, Script, OCR-A, OCR-B
<b>Characters</b>	Epson character sets, IBM code pages
<b>Attributes</b>	Italic, condensed, bold, double-strike, double-width, double-height, superscript, subscript, overscore, underscore
<b>Paper feed</b>	Push tractor or friction
<b>Paper path</b>	Rear (fanfold) or top (cut sheet)
<b>Paper weight</b>	53 to 105 g/m <sup>2</sup> (14 to 28lbs) Cut sheet : 64 to 105 g/m <sup>2</sup> (17 <sub>1</sub> to 28lbs)
<b>Paper width</b>	5" to 16" (fanfold & cut sheet)
<b>Multipart forms</b>	Original plus 8 duplicates
<b>Ribbon</b>	Special cassette-type black fabric ribbon (#BP-9000)
<b>Download</b>	Epson : 128 download characters IBM : 32 Kbytes
<b>Interface</b>	Centronics (parallel IEEE 1284 nibble), RS-232C (serial) USB (USB2.0 Full-speed), 10/100 Base-T Ethernet
<b>Printhead life</b>	500 million dots/pin (MCBF)
<b>Ribbon life</b>	20 million characters (#BP-9000)
<b>Power supply</b>	AC100-240V 50/60Hz
<b>Power consumption</b>	210 watts (maximum) 2 watts (sleep mode)
<b>Dimensions (W x D x H)</b>	620 x 350 x 260 mm (24.4" x 12.0" x 10.2") 620 x 455 x 295 mm (24.4" x 17.9" x 11.6") with paper rack and sound seal cover
<b>Weight</b>	Approx. 20kg (44.1 lbs)

\* Epson® is a registered trademark of Seiko Epson Corporation.

\* IBM® is a registered trademark of International Business Machines Corporation.

\* The specifications above are subject to be changed without notice.

## Take the Initiative - Choose the **au**i BP-9000E

Leadership in business demands certain qualities - proficiency, alacrity, and absolute professionalism.

Such are the characteristics that AUI BP-9000E printing, have to offer with its movable printhead, 2 emulations, barcode, 1+8 multipart forms capability, 7 resident LQ fonts, and 132 Kbyte data buffer.

At speeds of up to 846 cps (Super Speed Draft mode), it can handle even the most daunting print jobs without holding up the rest of your work. AUI BP-9000E is also equipped with a Zoom function which quickly and easily change the size of the printed characters to 50%~100%.

Most importantly however, the technical excellence is balanced by its superb operating ease. For any and all business needs, choose AUI BP-9000E - the printer that means business.

### Barcode printing

The AUI BP-9000E is also an ideal choice for barcode printing. The widespread adoption of these codes has led to significant increases in efficiency and accuracy, but high-quality printing is essential.

All major types of bar code can be output by AUI BP-9000E with speed and clarity : Industrial 2 of 5, Interleaved 2 of 5, Code 39, Code 128B, Code 128C, EAN-8, EAN-13 and NW-7.

### 2 level menu system

Operation is refreshingly simple, thanks to the innovative 2 level menu system (no DIP switches) which displays selections on LCD panel English. The AUI BP-9000E even stores 3 complete configurations for instant recall and provides detailed error message.

### Enhanced Interfaces

AUI BP-9000E is equipped with Parallel, Serial, USB and LAN interfaces.

### Flexible customization at request

**au**i AUI CO., LTD

4F, NOVEL WORK Bldg.,  
16-19 Nihombashi Kodemma-cho  
Chuo-ku, Tokyo, 103-0001 JAPAN  
TEL: +81-3-5640-1121  
FAX: +81-3-6231-1518  
URL: <http://www.aui.co.jp>  
E-mail: [pr-aui@au.co.jp](mailto:pr-aui@au.co.jp)